



www.sdcsecurity.com service@sdsecurity.com  
[t] 800.413.8783 805.494.0622 [f] 805.494.8861  
801 Avenida Acaso, Camarillo CA 93012 • PO Box 3670, Camarillo CA 93011-3670

## 25 Series Electric Strike

### 25 Series Electric Door Strike

- **Low Profile - 1.25" Backset**
- **Reversible Failsafe - Failsecure**
- **Latch Status Output Standard**

The SDC 25 Series electric strike is designed for use with cylindrical and mortise locksets with up to 5/8" (15mm) throw latchbolt. The compact low profile design with an internally mounted solenoid and factory supplied mounting tabs enable quick and easy installation where jamb space is limited. The heavy duty construction makes the 25 Series ideal for high traffic installations.

#### Features

- Fail-Secure
- Field reversible for failsafe operation
- For 1/2" latch or 5/8" latch with 1/8" door gap
- Latch status output, 3Amp - SPDT
- Non-handed, reversible
- All stainless steel parts with durable diecast body for corrosion resistance
- 630 Stainless steel standard finish
- ANSI A156.31 compliant

#### Model

**25-4U:** 4-7/8" (124mm) faceplate for aluminum, wood and hollow metal frames.




#### Options

**RMB** Buzzer 12/24V AC/DC operation  
**BR64XL** Rectifier for AC operation

#### Specifications

**Input:** 300/150 mA @ 12/24VDC  
**Latch Status:** SPDT, 3 Amp @ 30VDC  
**Dimensions:** 1-1/4" W x 4-7/8" H x 1-1/4" D  
(31.8W x 124H x 31.8D mm)

SECURITY DOOR CONTROLS



sdsecurity.com service@sdsecurity.com