



## Combination NGP-Edge® Sealing System Smoke and Draft Control Gasketing - Category 'G' and 'H' Listed

### 5050

#### Silicone Bulb Fire and Smoke Seal




**Edge Sealing System - Category "G"**  
**for 20 minute rated category B**  
**wood doors perimeter application up to:**  
single swing 4'0" x 8'0"  
pairs 8'0" x 8'0"  
use 9550 at the meeting edge of pairs




Up to 3 hours steel fire doors  
Up to 1 1/2 hours wood fire doors

Meets requirements of ROHS Directive 2002/95/EC



- 5050B** Brown
- 5050C** Charcoal
- 5050W** White
- 5050T** Tan
- 5050CL** Clear




Available in 17', 20', 21', 25', and 300' rolls

Self-Adhesive

Note: See adhesive specifications on next page

### Seal for Mullion Applications

- 5100N** Neoprene (black)
- 5100S** Silicone (gray)



Closed cell sponge strip 1-1/8" wide x 3/32" thick with an adhesive strip for mounting directly to the face of the mullion that doors close against.



Available in 86" and 96" lengths.

Self-Adhesive

Note: See adhesive specifications on next page

### Neoprene Sponge Self-Adhesive Gasketing

- |            | width     | thickness    |
|------------|-----------|--------------|
| <b>361</b> | 21' rolls | 3/8" x 3/16" |
| <b>362</b> | 21' rolls | 1/2" x 1/4"  |

